

100 TON

The Workhorse



Four Available Workstations
High Capacity Angle Shear
Universal Open Tooling Station

Electric Stroke Control
ANSI B11.5-1988R(02) Compliant
ETL/UL Approved Controls

If you're looking for versatility and power, the Edwards 100 Ton JAWS Ironworker is perfect for your shop. Standard features include a Punch Assembly, a 14" wide Flat Bar Shear, a high capacity Angle Shear and a universal open tooling station designed for optional Tooling Accessories allowing you to select the perfect tool for your needs.

PUNCH

Rating: 100 Tons
Max. Capacity: 1-1/16" Dia. in 1" A36
Stroke: 1-13/16"
Throat Depth: 11"
Open Height: 8-3/4"
Shut Height: 6-15/16"
Work Height: 39-1/16"

ANGLE SHEAR

Max. Capacity: 6" x 6" x 1/2"
Work Height: 43-15/16"

FLAT BAR SHEAR

Max. Capacity: 3/4" x 14"
1" x 10"
Max. Round: 1-1/4"
Max. Square: 1-1/4"
Work Height: 37"

OPEN STATION

Throat Depth: 14-3/4"
Open Height: 8-3/4"
Shut Height: 6-15/16"
Stroke: 1-13/16"
Work Height: 37"

OPTIONAL COPER NOTCHER

Max. Capacity: 2-1/2" x 6" x 1/2"
Work Height: 42"

GENERAL SPECIFICATIONS

Standard Motor: 7.5 HP 3~ 208 V or 230 V
1765 RPM 22 A
Optional Motors: 7.5 HP 3~ 460 V
1765 RPM 11 A
7.5 HP 3~ 575 V
1770 RPM 8 A
5 HP 1~ 208 V or 230 V
1725 RPM 23 A
*7.5 HP 1~ 208 V or 230 V
1765 RPM 36 A

**Required for 1~ Hydraulic Accessory Pack*

Hydraulic Pump: 10-1/2 GPM - 2 Stage
Valve Pressure: 3500 PSI
Reservoir: 17 Gallons
Cylinder: 3-1/2" Ram

DIMENSIONS

Height: 61-11/16"
Width: 56-1/8"
Depth: 45"
Shipping Weight: 4650 lb



Shown with
optional Coper Notcher

CALL (800) 373-8206

WWW.EDWARDSIRONWORKERS.COM